

# CASTERS



**SUPERIOR QUALITY SERVING THE MUSIC INDUSTRY**

## GRAND PIANO CASTERS

### FOR GRANDS

Solid brass 1-3/4" diameter wheels. Supplied with square CS1 pressed-steel sockets.

**No. 981** - Set of 3



### FOR GRANDS

Solid brass 1-3/8" diameter wheels. Supplied with square CS1 pressed-steel sockets.

**No. 980** - Set of 3



### FOR GRANDS

Solid brass, nickel plated 1-3/4" diameter wheels. Supplied with square CS1 pressed-steel sockets.

**No. 977** - Set of 3



### FOR GRANDS

Solid brass, nickel plated 1-3/8" diameter wheels. Supplied with square CS1 pressed-steel sockets.

**No. 2620** - Set of 3



## DUAL & SINGLE RUBBER WHEEL CASTERS

### FOR UPRIGHTS AND GRANDS

Twin Rubberex wheels with 2" diameter and 3/4" face on each wheel. Double ball-bearing swivel stem fits standard round or square, pressed steel sockets used on uprights and grands. Supplied with wood ferrules and pressed steel sockets. An excellent caster for pianos in churches and schools. Brown oxidized finish.

**No. 1592** - Set of 4 with round CR1 sockets

**No. 1592A** - Set of 3 with square CS1 sockets



### FOR UPRIGHTS AND GRANDS

Same description as No. 1592, except with single wheels with 2" diameter and 13/16" face on wheels. Brown oxidized finish.

**No. 1591** - Set of 4 with round CR1 sockets

**No. 1591A** - Set of 3 with square CS1 sockets



## UPRIGHT PIANO CASTERS

### FOR UPRIGHTS

Cast-iron 1-7/8" diameter wheels. Round cast-iron sockets are fixed in place.

**No. 589** - Set of 4



### FOR SPINETTS, CONSOLES, GRANDS

Brass-plated 1-3/8" diameter wheels. Supplied with round or square pressed-steel sockets.

**No. 982** - Set of 4 with round CR3 sockets

**No. 982A** - Set of 3 with square CS1 sockets



### FOR SMALL STUDIO UPRIGHTS

Cast-iron 1-3/8" diameter wheels. Supplied with round CR3 pressed steel sockets.

**No. 1588** - Set of 4



### FOR UPRIGHTS

Cast-iron 1-3/4" diameter wheels. Supplied with round CR3 pressed-steel sockets.

**No. 4588** - Set of 4



### FOR SPINETTS OR CONSOLES

Solid brass 1-1/4" diameter wheels, 11/16" face, for the front free legs. Supplied with CR7 plastic sockets.

**No. 978** - Set of 4



### FOR SPINETTS OR CONSOLES

Brass-plated 1-1/4" diameter wheels, 9/16" face, for the front free legs. Supplied with CR7 plastic sockets.

**No. 979** - Set of 4



# CASTERS



**DARNELL SUPERIOR QUALITY CASTERS. - FEATURES A HEAVY DUTY DURABLE BALL BEARING SYSTEM. EXCELLENT FOR SCHOOLS, CHURCHES OR ANY FACILITY THAT MOVES PIANOS FREQUENTLY. SINGLE WHEELS RATED AT 100 LB LOAD CAPACITY. DUEL WHEELS RATED AT 200 LB LOAD CAPACITY.**

## FOR UPRIGHTS

Single, rubber-fibre wheel with 2" diameter and 1" face. Features a double ball-bearing swivel; upper row carries load weight, and lower row the side thrust. Supplied with removable, round CP1C, cast-iron sockets with 4 screw holes.

**No. 591** - Set of 4



## FOR UPRIGHTS

Same description as No. 591 except with twin rubber-fibre wheels with 2" diameter and 3/4" face on each wheel. CP1C sockets.

**No. 592** - Set of 4



## FOR UPRIGHTS AND GRANDS

Single, rubber fibre wheel with 2" diameter and 1" face. Features a double ball-bearing swivel; upper row carries the load weight, and lower row takes up all the side thrust. Standard stem (.435 x 1-3/8") for use with round CR3 or square CS3, pressed-steel sockets.

**No. 2591** - Set of 4 with round CR3 sockets

**No. 2591A** - Set of 3 with square CS3 sockets



## FOR UPRIGHTS AND GRANDS

Same description as No. 2591 except with twin, rubber fibre wheels with 2" diameter and 3/4" face on each wheel.

**No. 2592** - Set of 4 with round CR3 sockets

**No. 2592A** - Set of 3 with square CS3 sockets



## FOR GRANDS

Single, rubber-fibre wheel with 2" diameter and 1" face. Features a double ball-bearing swivel; upper row carries the load weight, and lower row takes up all the side thrust. Supplied with removable, square CP2C, cast-iron sockets with 4 screw holes.

**No. 591A** - Set of 3



## FOR GRANDS

Same description as No. 591A except with twin, rubber-fibre wheels with 2" diameter and 3/4" face on each wheel. Supplied with removable square CP2C, cast-iron sockets with 4 screw holes.

**No. 592A** - Set of 3



## FOR STEINWAY UPRIGHTS AND GRANDS

2" diameter, solid brass wheel with a 1" face and a 1/2" diameter friction ring stem.

**No. 596** - Set of 4 with round CP-1C sockets

**No. 596A** - Set of 3 with square CP-2C sockets



1-1/2" diameter solid brass wheel with a 3/4" face and a 1/2" diameter friction ring stem.

**No. 597** - Set of 4 with round CP-1C sockets

**No. 597A** - Set of 3 with square CP-2C sockets



## PRESSED STEEL SOCKETS

### PRESSED STEEL ROUND

2-1/8" diameter without lock notch, for use with our No. 1591+1592 only.

**No. CR1** - Each



### PRESSED STEEL ROUND

2-1/8" diameter.

**No. CR3** - Each



### PRESSED STEEL ROUND

1-3/8" diameter.

**No. CR5** - Each



### PRESSED STEEL SQUARE

1-5/8".

**No. CS1** - Each



### PRESSED STEEL SQUARE

1-1/2".

**No. CS3** - Each



## CASTER SOCKETS

### PLASTIC ROUND

1" Furniture Stem for use with our No. 978+979 casters only.

**No. CR7** - Each



### CAST METAL SOCKETS

For use with Darnell friction ring stems.

**No. CP1C** - Cast Metal Round

2-1/4" diameter. Each

**No. CP2C** - Cast Metal Square

1-13/16". Each



### WOOD CASTER BUSHINGS

To insert in the holes left by old style cast iron caster sockets when installing modern stem casters.

**No. CWF** - Each



### CARDBOARD CASTER WASHERS

Used to level pianos or shimming caster sockets. 1-3/4" O.D., 3/4" hole, .125" thick.

**No. 1670** - Each



# SOLID BRASS CASTERS

An exacting replacement. Imported from Europe. sold **EACH**

## GRAND CASTER

**No. 2600** - 1" Wheel width  
2" Wheel diameter  
7/8" Socket diameter



## GRAND CASTER

**No. 2602** - 2-3/8" Wheel width  
1-7/8" Wheel diameter  
13/16" Socket diameter



## GRAND CASTER

**No. 2604** - 2-3/8" Wheel width  
1-7/8" Wheel diameter  
1-1/8" Socket diameter



## CONCERT GRAND CASTER

**No. 2605A** - 3-3/8" Wheel width  
3-1/2" Wheel diameter  
1-1/8" Socket diameter

**No. 2605B** - Same dimensions as above except with brake.



## GRAND CASTER

**No. 2601** - 1-1/2" Wheel width  
1-7/8" Wheel diameter  
13/16" Socket diameter



## GRAND CASTER WITH FERRULE

**No. 2603** - 2" Wheel width  
1-3/4" Wheel diameter  
13/16" Socket diameter  
2" Inside width of ferrule



## CONCERT GRAND CASTER

**No. 2610A** - 5-3/8" Wheel width  
3-3/4" Wheel diameter  
13/16" Socket diameter

**No. 2610B** - Same dimensions as above except with brake.



## RESTORERS & TREATMENTS

### LUNSFORD'S INSTANT PIN-TITE

Tightens in MINUTES, restores pin block permanently, preserves and protects wood, remains dry, tune within hour - 20 minutes in many cases, and also tightens instantly many action parts, cases, benches, and stripped screw holes. 8 oz Bottle.

**No. 1347** - Each



### HAMMER FELT HARDENER

Lacquer free formula. May be applied to the shoulders of the hammer as well as the striking surface. 8 oz. Bottle.

**No. 1404** - Each.



### "BRITE-TONE" HAMMER HEAD SOLIDIFIER

For restoring lost tone to soft hammers. In use, apply a small amount along top and bottom surface of hammer to within 1/2" of striking point. Do not apply on striking surface.

**No. 499-2** - 2 oz. Bottle. Each

**No. 499-8** - 8 oz. Bottle. Each



### GARFIELD PIN BLOCK RESTORER

This success of GARFIELD PIN BLOCK RESTORER has brought about many imitations. There is only one original and genuine GARFIELD Restorer - made by a formula developed by Wm. M. Garfield after 40 years' experience as a tuner and technician. For your own protection, insist upon it. GARFIELD'S PIN BLOCK RESTORER has these important features: It comes in liquid form...easy to apply with a syringe or eye dropper. It penetrates into the cells of the wood to restore its holding power. It contains no oil...will not evaporate. Its effectiveness improves with age...in one week the pins are tight enough to permit tuning. It prevents rust...will not affect glue. 4 oz bottle. Must be diluted with equal amounts of denatured alcohol.

**No. 1346** - Each

